Journal of Testing and Evaluation
Author Index to Volume 18
1990

Number	Month of Issue	Pages
1	January	1–86
2	March	87–140
3	May	141–228
4	July	229–308
5	September	309–372
6	November	373–466

A–B

Addassi, E: *see* Ragab, AR, Alawi, H and Addassi, E

Al-Otaibi, K. M.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.

Alawi, H: *see* Ragab, AR, Alawi, H and Addassi, E

Banerjee, G: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G

Barker, L. M.: *see* Munz, D. and Barker, L. M.

Bashu, SA: Impact energy/specimen thickness relationship for two turbine steels, Sept., 363

Baxter, WJ: Imaging short fatigue cracks with the gel electrode, Nov., 430

Berens, AP and Watanabe, RT: Introduction to symposium on quantitative methods in the assessment of structural defects, Nov., 420

Biron, A: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN

Brinkley, JW: *see* Sulowski, AC and Brinkley, JW

Bucci, RJ: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL

Buck, O: *see* Rehbein, DK, Thompson, RB, and Buck, O

Bui-Quoc, T, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN: Cyclic stress-strain behavior and low cycle fatigue of Ti6242, May, 160

C–D

Clark, T. R., Hertzberg, R. W., and Manson, J. A.: Influence of test methodology on fatigue crack propagation in engineering plastics, Sept., 319

Crosley, PB and Ripling, EJ: A quality control test for selecting materials to arrest fast-running, full-thickness cracks, Nov., 396

Dally, JW and Sanford, RJ: Measuring the stress intensity factor for propagating cracks with strain gages, July, 240

Das, PK: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G

Das, SK: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON

Das, SK, Ghosh, A, Das, PK and Banerjee, G: An appraisal of hydration characteristics of dead burnt dolomite grains, Jan., 76

Davis, G. B. and Schroeder, L. W.: Influence of contact angles on the leakage of latex condoms, Sept., 352

Davis, DC: An approach to predicting long-term toughness, strength, and ductility of a Cr-Mo-V steel alloy using short-term tests, July, 286

DuQuesnay, DL: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT *see* Yu, MT, DuQuesnay, DL and Topper, TH

E–G

Ernst, HA: *see* Wert, MJ, Saxena, A and Ernst, HA

Ghosh, A: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G

Goddard, MJ: *see* Malaiyandi, M and Goddard, MJ

Gomuc, R: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN

Gope, PC: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON

Gordon, JR: *see* Smith, DJ and Gordon, JR

Grabovac, I: *see* Wycherley, GW, Mestan, SA and Grabovac, I

Groth, HL and Zenkert, D: Fracture of defect foam core sandwich beams, Nov., 390

H–J

Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW: The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates, Jan., 62

Hartwig, KT, Jr.: *see* Richards, GL and Hartwig, KT, Jr.

Hellmann, JR: *see* Segall, AE, Hellmann, JR and Strzepa, P

Hertzberg, RW: *see* Clark, T. R., Hertzberg, R. W., and Manson, J. A.

Hinkle, AJ: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL

Hirth, JP: *see* Manoharan, M, Hirth, JP and Rosenfield, AR

Inukai, T: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H

Jhansale, HR and McCann, DR: Bore inspection and life evaluation of vintage steam turbine/generator rotors, Nov., 446

Jiang, B. and Shao, E.: A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials, Sept., 328

Joyce, JA: Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel, Nov., 373

Jung, Y.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.

K–L

Kain, R. M.: Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies, Sept., 309

Kaiser, WT: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL

Kasal, D: *see* White, MS, McLain, TE, Padla, D and Kasal, B

Kashiwaya, H: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H

Kimura, K, Inukai, T, Saito, K and Kashiwaya, H: Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel, May, 172

Kirk, M. T. and Sanford, R. J.: A K_I calibration for a modified single edge notched tension specimen, Sept., 344

Lau, PWC and Tardif, Y: A computer-aided image system for analyzing cracks created by nailing in wood, March, 131

Leon-Salamanca, T.: Review of *Nondestructive Testing (Metallurgy and Materials Science)*, July, 305

Leung, C–P, McDowell, DL and Saxena, A: Estimation of the C_t parameter: experimental implications, Jan., 25

Liao, K. C.: Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application, Sept., 338

Little, RE: Optimal stress amplitude selection in estimating median fatigue limits using small samples, March, 115

Lucas, GE: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW

M

Macdonald, BD and Pajot, JJ: Stress intensity factors for side-grooved fracture specimens, July, 281

Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL: Durability assessment based on initial material quality, Nov. 439

Mahboub, K: Elasto-plastic fracture characterization of paving materials at low temperatures, May, 210

Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.: Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25Cr-1Mo steel, Sept., 332

Malaiyandi, M and Goddard, MJ: Development of analytical methodology and a

report on collaborative study on the determination of morpholine, cyclohexylpamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography, March, 87

Manoharan, M, Hirth, JP and Rosenfield, AR: A suggested procedure for combined mode I–mode III fracture toughness testing, March, 106

Manson, J. A.: *see* Clark, T. R., Hertzberg, R. W., and Manson, J. A.

McCann, DR: *see* Jhansale, HR and McCann, DR

McDowell, DL: *see* Leung, C-P, McDowell, DL and Saxena, A

McGlone, FB: Review of *AIDS and Intravenous Drug Use: Future Directions for Community-Based Prevention Research,* Nov., 458

McLain, TE: *see* White, MS, McLain, TE and Padla, D
see White, MS, McLain, TE, Padla, D and Kasal, B

McNatt, JD and Soltis, LA: Instrumented impactor for testing wood-base floor panels, July, 265

Meredith, SE and Schemel, JH: Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing, March, 98

Mestan, SA: *see* Wycherley, GW, Mestan, SA and Grabovac, I

Mohanty, ON: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON

Mones, E: Review of *Handbook of Environmental Fate and Exposure Data for Organic Chemicals,* Nov., 458

Munz, D. and Barker, L. M.: Discussion of "Chevron-notched specimens for fracture toughness measurements independent of *R*-curve effects," with author's closure, Sept., 369

Murty, K. L.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.

N–R

Nguyen, HL: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN

Nishimura, T, Noguchi, Y, and Uchimoto, T: Damage tolerance analysis of multiple-site cracks emanating from hole array, Nov., 401

Noguchi, T: Bending strength of gray cast iron, Jan., 70

Noguchi, Y: *see* Nishimura, T, Noguchi, Y, and Uchimoto, T

Odette, GR: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW

Padla, D: *see* White, MS, McLain, TE and Padla, D
see White, MS, McLain, TE, Padla, D and Kasal, B

Pajot, JJ: *see* Macdonald, BD and Pajot, JJ

Parida, N, Das, SK, Gope, PC, and Mohanty, ON: Probability, confidence, and sample size in fatigue testing, Nov., 385

Pellicane, PJ: Behavior of rubber-based elastomeric construction adhesive in wood joints, July, 256

Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT: Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum, Jan., 53

Purtscher, PT: *see* Rosenthal, YA, Tobler, RL and Purtscher, P

Putatunda, SK and Venugopal, V: Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution, May, 182

Ragab, AR, Alawi, H and Addassi, E: Weathering effects on some mechanical properties of polyvinyl chloride pipes, Jan., 45

Rehbein, DK, Thompson, RB, and Buck, O: Fatigue crack characterization by ultrasonic inspection, Nov., 421

Richards, GL and Hartwig, KT, Jr.: A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements, Nov., 454

Ripling, EJ: *see* Crosley, PB and Ripling, EJ

Rolf, RL: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL

Rosenfield, AR: *see* Manoharan, M, Hirth, JP and Rosenfield, AR

Rosenthal, YA, Tobler, RL and Purtscher, PT: J_R data analysis methods with a "negative crack growth" correction procedure, July, 301

S

Saito, K: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H

Sanford, R. J.: *see* Kirk, M. T. and Sanford, R. J.

Schroeder, L. W.: *see* Davis, G. B. and Schroeder, L. W.

Sanford, RJ: *see* Dally, JW and Sanford, RJ

Santner, JS: Use of cantilever specimens to determine microcreep properties, May, 191

Saxena, A: *see* Leung, C-P, McDowell, DL and Saxena, A
see Wert, MJ, Saxena, A and Ernst, HA

Schemel, JH: *see* Meredith, SE and Schemel, JH

Scherrer, DK: *see* Taylor, JA and Scherrer, DK

Segall, AE, Hellmann, JR and Strzepa, P: Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state, July, 250

Seligson, D: Historical overview of femoral intramedullary nailing, March, 138

Server, WL: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW

Shao, E.: *see* Jiang, B. and Shao, E.

Shapiro, JM: *see* Sharpe, WN, Jr., and Shapiro, JM

Sharpe, WN, Jr., and Shapiro, JM: Dynamic *K* measurements in three-point-bend specimens, Jan., 38

Sheckherd, JW: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW

Slatcher, S: Estimation of characteristic values of fracture toughness, May, 141

Smith, DJ and Gordon, JR: The linearity of clip gages used in fracture mechanics tests, Jan., 14

Soltis, LA: *see* McNatt, JD and Soltis, LA

Strzepa, P: *see* Segall, AE, Hellmann, JR and Strzepa, P

Sulowski, AC and Brinkley, JW: Measurement of maximum arrest force in performance tests of fall protection equipment, March, 123

T–V

Tadros, RN: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN

Tardif, Y: *see* Lau, PWC and Tardif, Y

Taylor, JA and Scherrer, DK: Plastic strain ratio (*r*) for sheet metal: effect of gage length and width measurement locations using reduced section specimens, July, 292

Thompson, RB: *see* Rehbein, DK, Thompson, RB, and Buck, O

Tobler, RL: *see* Rosenthal, YA, Tobler, RL and Purtscher, PT

Topper, TH: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MI
see Yu, MT, DuQuesnay, DL and Topper, TH

Uchimoto, T: *see* Nishimura, T, Noguchi, Y, and Uchimoto, T

Ukponmwan, JO: Changes in cotton fabric bending properties as a result of laboratory wear, Nov., 408

Urbanik, T. J.: Force plate for corrugated container vibration tests, Sept., 359

Venugopal, V: *see* Putatunda, SK and Venugopal, V

W–Z

Watanabe, RT: *see* Berens, AP and Watanabe, RT

Weiler, WW: Dynamic loading: a new microhardness test method, July, 229

Wert, MJ, Saxena, A and Ernst, HA: Applicability of modified *J* as a fracture parameter for polycarbonate, Jan., 1

White, MS, McLain, TE and Padla, D: Relationships between the results of nail impact bend tests and selected nail material properties, May, 219

White, MS, McLain, TE, Padla, D and Kasal, B: Hardness gradients within rolled-threaded steel nails, March, 128

Wickstrom, SN and Wolfenden, A: Measurements of dynamic Young's modulus in short specimens with the PUCOT, Jan., 81

Wolfenden, A: *see* Wickstrom, SN and Wolfenden, A

Wycherley, GW, Mestan, SA and Grabovac, I: A method for uniform shear stress-strain analysis of adhesives, May, 203

Yu, MT: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT

Yu, MT, DuQuesnay, DL and Topper, TH: Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel, July, 274

Zenkert, D: *see* Groth, HL and Zenkert, D

Journal of Testing and Evaluation
Subject Index to Volume 18
1990

A

Adhesives
A method for uniform shear stress-strain analysis of adhesives (Wycherley, Mestan and Grabovac), May, 203
Aluminum
Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439
Anisotropy
Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98
Arrest force
Measurement of maximum arrest force in performance tests of fall protection equipment (Sulowski and Brinkley), March, 123
Asphalt
Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210
ASTM C 273
Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390
ASTM Method E 813-87
J_c data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler and Purtscher), July, 301

B

Ball indentation test
The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Sheckherd), Jan., 62
Bend
Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332
Bending strength
Bending strength of gray cast iron (Noguchi), Jan., 70
Book reviews
AIDS and Intravenous Drug Use: Future Directions for Community-Based Prevention Research (McGlone), Nov., 458
Handbook of Environmental Fate and Exposure Data for Organic Chemicals (Mones), Nov., 458
Nondestructive Testing (Metallurgy and Materials Science (Leon-Salamanca), July, 305
Brittle
An approach to predicting long-term toughness, strengh, and ductility of a Cr-Mo-V steel alloy using short-term tests (Davis), July, 286

C

Carbon content
Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219
Clip gage
The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14
Cold rolling
Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, DuQuesnay and Topper), July, 274
Combined mode fracture
A suggested procedure for combined mode I–mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106
Confidence level
Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385
Constitutive equation
An approach to predicting long-term toughness, strengh, and ductility of a Cr-Mo-V steel alloy using short-term tests (Davis), July, 286
Continuous annealing
Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application (Liao), Sept., 338
Contractile strain ratio
Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98
Conventional
A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials (Jiang and Shao), Sept., 328
Copper
Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81
Crack
Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, DuQuesnay and Topper), July, 274
Crack arrest
A K_1 calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344
Crack arrest fracture toughness
A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396
Crack closure
Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53
Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421
Crack propagation
A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131
Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401
Creep
Estimation of the C_t parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25
Creep crack growth
Estimation of the C_t parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25
Creep rupture
An approach to predicting long-term toughness, strength, and ductility of a Cr-Mo-V steel alloy using short-term tests (Davis), July, 286
Crevice corrosion
Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309
Critical review
Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309
Crystallographic texture
Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98
C_t parameter
Estimation of the C_t parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25
CTOD
Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38
Estimation of characteristic values of fracture toughness (Slatcher), May, 141
Cyclic J
Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373
Cyclic stress-strain
Cyclic stress-strain behavior and low cycle fatigue of Ti6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160

Cyclohexylamine
Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87

D

Damage
Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53
Dead burnt dolomite
An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76
Degradation
Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172
Degradation of PVC
Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45
Densification
An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76
Diethylaminoethanol
Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87
Displacement transducer
The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14
Durability
Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439
Duration of exposure
Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256
Dynamic contact angle
Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352
Dynamic fracture
Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240
Dynamic microhardness testing
Dynamic loading: a new microhardness test method (Weiler), July, 229
Dynamic modulus
Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81
Dynamic testing
Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38

E

Eddy-current decay method
A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454
Elastic fracture specimens
Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281
Elastic-plastic fracture
Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373
Elastomeric adhesives
Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256
Electrical resistivity
A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454

F

Fall protection
Measurement of maximum arrest force in performance tests of fall protection equipment (Sulowski and Brinkley), March, 123
Fatigue
Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439
Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53
Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, DuQuesnay and Topper), July, 274
Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421
Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319
Fatigue crack
Imaging short fatigue cracks with the gel electrode (Baxter), JOTE, Nov., 430
Fatigue life
Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385
Femoral
Historical overview of femoral intramedullary nailing (Seligson), March, 138
Flexure test
Bending strength of gray cast iron (Noguchi), Jan., 70
Floors
Instrumented impactor for testing wood-base floor panels (McNatt and Soltis), July, 265
Fracture
A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131
Fracture mechanics
A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131
A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396
Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1
The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14
Fracture testing
Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210
Fracture toughness
A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396
A suggested procedure for combined mode I–mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106
Estimation of characteristic values of fracture toughness (Slatcher), May, 141
J_{ic} data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler and Purtscher), July, 301

G

Gel electrode imaging
Imaging short fatigue cracks with the gel electrode (Baxter), JOTE, Nov., 430
Generator rotors
Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446
Gradients
Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128
Gray cast iron
Bending strength of gray cast iron (Noguchi), Jan., 70

H

Hardness
Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128

I

Impact tests
Measurement of maximum arrest force in performance tests of fall protection

equipment (Sulowski and Brinkley), March, 123
Incubation period
Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182
Instrumented impact testing
Instrumented impactor for testing wood-base floor panels (McNatt and Soltis), July, 265
Interferometry
Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38
Intramedullary nailing
Historical overview of femoral intramedullary nailing (Seligson), March, 138
Iosipescu method
A method for uniform shear stress-strain analysis of adhesives (Wycherley, Mestan and Grabovac), May, 203

J

***J* integral**
Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1
J_R data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler, and Purtscher), July, 301

L

Latex
Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352
Low carbon steels
Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application (Liao), Sept., 338
Low cycle fatigue
Cyclic stress-strain behavior and low cycle fatigue of Ti 6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160
Low cycle fatigue crack growth
Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373

M

Mean stress
Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319
Median fatigue limits
Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115
Method
A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials (Jiang and Shao), Sept., 328
Microcreep testing
Use of cantilever specimens to determine microcreep properties (Santner), May, 191
Microhardness testing under load
Dynamic loading: a new microhardness test method (Weiler), July, 229
Microstress relaxation (MSR)
Use of cantilever specimens to determine microcreep properties (Santner), May, 191
Miniaturized tests
The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Sheckherd), Jan., 62
Minimum variance strategy
Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115
Mixed-mode fracture
A suggested procedure for combined mode I–mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106
Morpholine
Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87
Multiple crevice
Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309
Multiple-site cracks
Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401
Multistep cycling
Cyclic stress-strain behavior and low cycle fatigue of Ti6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160

N

Nails
Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128
Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219
Natural weathering of PVC
Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45
Nondestructive test
Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172

O

Optimum allocation of specimens
Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115
Overload
Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182

P

Pavement materials
Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210
Percentage difference
Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408
Percentage loss in weight
Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408
Photoelasticity
A K_I calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344
Plywood
Instrumented impactor for testing wood-base floor panels (McNatt and Soltis), July, 265
Polycarbonate
Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1
Polyvinyl chloride pipe
Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45
Preshipment container
Force plate for corrugated container vibration tests (Urbanik), Sept., 359
Pressure vessel steels
Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332
Probability
Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385

R

***r*-value**
Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292
Rapid
A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials (Jiang and Shao), Sept., 328

Relaxation time
A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454

S

Sandwich beams
Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390
Sandwich structures
Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390
Shear punch test
The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Sheckherd), Jan., 62
Shear test
A method for uniform shear stress-strain analysis of adhesives (Wycherley, Mestan and Grabovac), May, 203
Shipping environment
Force plate for corrugated container vibration tests (Urbanik), Sept., 359
Shirley cyclic bending tester
Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408
Shock and vibration
Force plate for corrugated container vibration tests (Urbanik), Sept., 359
Short crack growth
Imaging short fatigue cracks with the gel electrode (Baxter), Nov., 430
Side-grooving
Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281
Single crystals
Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81
Spindles
Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446
Splints
Historical overview of femoral intramedullary nailing (Sehgson), March, 138
Stable members
Use of cantilever specimens to determine microcreep properties (Santner), May, 191
Static contact angle
Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352
Statistics
Estimation of characteristic values of fracture toughness (Slatcher), May, 141
Steady-state
Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state (Segall, Hellmann and Strzepa), July, 250
Steam turbine
Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446
Strain gage
Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240
Stress corrosion cracking
Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182
Stress intensity factor
A K_I calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344
Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401
Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240
Stress intensity factors
Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281
Sub-size specimens
Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363

T

Temperature effects
Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256
Tensile
Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332
Thermal profiles
Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state (Segall, Hellmann and Strzepa), July, 250
Thermoelastic stress
Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state (Segall, Hellmann and Strzepa), July, 250
Threshold
Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319
Tin mill products
Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application (Liao), Sept., 338
Toughness
Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172
Turbine steels
Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363
Two-stage calcination
An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76
Type A alternative specimens
Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292
Type A standard specimens
Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292

U

Ultra-low load microhardness testing
Dynamic loading: a new microhardness test method (Weiler), July, 229
Ultrasonic
Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421

V

V-notch Charpy impact test
Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363

Y

Yield strength
Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219